



FEARLESS PERFORMANCE™

CE ATITIKTIES DEKLARACIJA

galiotas atstovas:
Granberg AS
Bjoavegen 1442
NO-5584 Bjoa
NORVEGIJA

Gamintojas:
Granberg AS
Bjoavegen 1442
NO-5584 Bjoa
NORVEGIJA

Deklaruoja, kad:

Art. 114.955



EN 420:2003



AQL

1.5

EN 374:2003



EN 374-2



EN 1186



atitinka 1989 m. gruodžio 21 d. 89/686/EEB Direktyvos nuostatas (d l asmens apsaugini priemoni atitikimo 8 Straipsnio 3 paragrafui) ir nacionalinius standartus atitinkan ius darniuosius standartus,

kurie buvo taikomi CE tipo tyrimui. CE atitikties sertifikat išdav notifikuota staiga:

SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, Jungtin Karalyst

Ole Marthon Granberg
Generalinis direktorius

Bjoa, 25.09.2018



FEARLESS PERFORMANCE™

GRANBERG AS

Bjoavegen 1442
NO-5584 Bjoa
NORWAY

TELEPHONE, FAX

+47 53 77 53 00
+47 53 77 53 01
NORWAY

E-MAIL

service@granberg.no

ORGANISATION NO.

NO 947 780 093 MVA

www.granberg.no



FEARLESS PERFORMANCE®

EC DECLARATION OF COMPLIANCE

The authorized agent:

Granberg AS
Bjoavegen 1442
NO-5584 Bjoa
NORWAY

Acting for the manufacturer:

Granberg AS
Bjoavegen 1442
NO-5584 Bjoa
NORWAY

Hereby declares that:

Art. 114.955



EN 420:2003



AQL

1,5

EN 374:2003



EN 374-2



EN 1186




..is in conformity with the provisions of Directive 89/686/EEC of 21 December 1989 (for the personal protective equipment referred to in Article 8 paragraph 3) and with national standards transposing harmonized standards:

... has been subject of EC type examination. EC compliance certificate delivered by the notified body:

[SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom](#)

Ole Marthon Granberg
Managing Director

Bjoa, issued on 25.09.2018



FEARLESS PERFORMANCE®

GRANBERG AS

Bjoavegen 1442
NO-5584 Bjoa
NORWAY

TELEPHONE, FAX

+47 53 77 53 00
+47 53 77 53 01
NORWAY

E-MAIL

service@granberg.no

ORGANISATION NO.

NO 947 780 093 MVA

www.granberg.no

ENGLISH

Single-Use Gloves. Nitrile, powder-free. Blue colour. 30 cm length.

EU Type-Examination

- This product is classed as Complex Design of Personal Protective Equipment (PPE) according to European PPE Regulation (EU) 2016/425 and has been shown to comply with this Regulation through the Harmonised European Standards EN 420:2003+A1:2009, EN ISO 374-1:2016 and EN ISO 374-5:2016.
- Notified Body responsible for certification and Module B compliance is SATRA Technology Centre Ltd, Wyndham Way, Kettering NN16 8SD, UK. Notified body number 0321.
- Notified Body responsible for EC Quality Control System for the Final Product and compliance to Module D is SATRA Technology Centre Ltd, Wyndham Way, Kettering NN16 8SD, UK. Notified body number 0321.

EN ISO 374-1:2016 permeation levels are based on breakthrough times as follows:

Performance level	1	2	3	4	5	6
Minimum Breakthrough time (mins)	≥ 10	≥ 30	≥ 60	≥ 120	≥ 240	≥ 480

EN ISO 374-1:2016/Type B



Chemical Hazards Pictogram: EN 16523-1:2015; Additional information on chemical resistance obtainable from manufacturer. This product complies with Type B requirements and the following pictogram shall be used with reference to clause 6.3 of ISO 374-1.

EN ISO 374-5:2016



Micro Organism Hazards Pictogram: EN ISO 374-5:2016 - Protection against Bacteria, Fungi and Virus. If there is no penetration of bacteriophages through the specimen, the following pictogram is applied.

AQL is 1.5; Additional information obtainable from the manufacturer.



Gloves are in compliance with the Regulation (EC) 1935:2004 and are suitable for handling all kinds of foodstuffs for short period of time.

Performance and Limitation of Use

- This product has been tested in accordance with EN ISO 374-5:2016. Protection against bacteria and fungus - Pass. Protection against virus - Not assessed..
- Gloves had been tested in accordance with EN 16523-1:2015 resistance to permeation by chemicals and in accordance with EN 374-4:2013.

EN ISO 374-1:2016 (Type B)	Level	EN 374-4:2013 Degradation, %
O 25% Ammonium Hydroxide	2	6.6
J n-Heptane	6	19.5
K 40% Sodium Hydroxide	6	-13.5
P 30% Hydrogen Peroxide	6	27.0
T 37% Formaldehyde	6	20.1

- This information does not reflect the actual duration of protection in the workplace and the differentiation between mixtures and pure chemicals.
- The chemical resistance has been assessed under laboratory conditions from samples taken from the palm only (except in cases where the glove is equal to or over 400mm – where the cuff is tested also) and relates only to the chemical tested. The result may differ if the chemical is used in a mixture.
- It is recommended to check that the gloves are suitable for the intended use because the conditions at the workplace may differ from the type test depending on temperature, abrasion and degradation.
- When used, protective gloves may provide less resistance to the dangerous chemical due to changes in physical properties. Movements, snagging, rubbing, degradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves.

Before usage, inspect the gloves for any defect or imperfections.

EN 374-4:2013 Degradation levels indicate the change in puncture resistance of the gloves after exposure to the challenge chemicals.

- This product provides against Bacteria, Fungi and Virus. The gloves had been tested in accordance with ISO 16604:2014 (the test method is uses Phi-X174 bacteriophages) to meet the requirements of BS EN ISO 374-5:2016 for resistance to penetration by blood-borne pathogens. The penetration resistance has been assessed under laboratory conditions and relates only to the tested specimen.
- Components used in glove manufacturing may cause allergic reactions in some users. If allergic reactions occur, seek for medical advice immediately.

Product Instruction for Use

- Usage – For Single Use only. If re-used, the risk of contamination and infection increases due to improper cleaning processes; and increased risk of holes and tear during re-use due to weakening of gloves by cleaning processes.
- Sizing – Select the right size glove for your hand.
- Donning – Hold glove by the bead with one hand. Align the glove thumb with your other hand thumb and slide your hand into the glove, one finger into each glove finger. Pull by the glove palm to a get a good fit. Don the other glove by the same procedure.
- Inspection – Punctures or tears may occur after donning. Inspect each glove after donning, and immediately discontinue use if found damaged.
- During Use - Gloves polluted by blood or other organic fluids must be immediately removed as medical waste. In case of pricking or tearing, user should immediately change gloves.
- In case of feeling looseness on fingers, user should change gloves.
- Doffing – Hold glove bead and pull toward the finger until the glove come off.

Storage Conditions

Store in a cool and dry place. Opened boxes should be kept away from fluorescent and sunlight.

Ideally stored in dry conditions.

When stored as recommended, the gloves will not suffer any changes in chemical properties for up to three years from date of manufacture. Service life cannot be specified and depends on application and responsibility of user to ascertain suitability of the glove for its intended use.

NORSK

Engangshansker. Nitril, puddefri. Blå farge. 30 cm lengde

EC typegodkjenning

- Dette produktet er klassifisert som en kompleks utforming av personlig verneutstyr (PVU) i henhold til europeisk PVU forskrift (EU) 2016/425 og etterkommer forskriften gjennom de harmoniserte europeiske standardene EN 420:2003+A1:2009, EN ISO 374-1:2016 og EN ISO 374-5:2016.
- Det tekniske kontrollorganet som er ansvarlig for sertifisering og samsvar med modul B, er SATRA Technology Centre Ltd, Wyndham Way, Kettering NN16 8SD, UK. Laboratorienummer 0321.
- Ansvarlig laboratorie for testing av EC kvalitetskontroll-system for sluttproduktet og etterlevelse av modul D er; SATRA Technology Centre Ltd, Wyndham Way, Kettering NN16 8SD, UK. Laboratorienummer 0321.

EN 374-1:2016 gjennomtrengningsnivåer er basert på gjennombruddstider som følger:

Ytelsesnivå	1	2	3	4	5	6
Minimum gjennombruddstid (minutter)	≥ 10	≥ 30	≥ 60	≥ 120	≥ 240	≥ 480

EN ISO 374-1:2016/Type B



Piktogram for kjemiske farer: EN 16523-1:2015; Ytterligere informasjon om kjemisk motstand fås fra produsentens. Dette produktet oppfyller kravene til Type B og følgende piktogram må benyttes med henvisning til klausul 6.3 i ISO 374-1.

EN ISO 374-5:2016



Piktogram for farer relatert til mikroorganismer: EN ISO 374-5:2016 - Beskyttelse mot bakterier, sopp og virus. Om det ikke er noen penetrasjon av bakteriofager gjennom prøven kan følgende piktogram påføres.

AQL er 1.5; Utfyllende informasjon er tilgjengelig fra produsenten.



Hanskene er i samsvar med forskriften (EC) 1935:2004 og er egnet til å håndtere alle typer matvarer i kort tid.

Ytelse og bruksbegrensning

- Dette produktet er testet i henhold til EN ISO 374-5:2016. Beskyttelse mot bakterier og sopp – Godkjent. Beskyttelse mot virus - Ikke vurdert.
- Hanskene er testet i henhold til EN 16523-1:2015 - Motstand mot gjennomtrengning av kjemikalier, og i samsvar med EN 374-4:2013.

EN ISO 374-1:2016 (Type B)	Nivå	EN 374-4:2013 Degradation, %
O 25% Ammoniumhydroksid	2	6.6
J n-Heptan	6	19.5
K 40% Natriumhydroksid	6	-13.5
P 30% Hydrogenperoksid	6	27.0
T 37% Formaldehyd	6	20.1

- Denne informasjonen gjenspeiler ikke den faktiske varigheten av beskyttelsen på arbeidsplassen og skillet mellom blandinger og rene kjemikalier.
- Den kjemiske motstanden har blitt vurdert under laboratoriebetingelser fra prøver på håndflaten (unntatt i tilfeller hvor hanskene er lik eller over 400 mm - hvor på mansjettene også testes) og gjelder bare for den spesifikke kjemikalien som er testet. Resultatet kan være annerledes om kjemikallet benyttes i en blanding.
- Det anbefales å kontrollere at hanskene er egnet for den tilskilte bruken fordi forholdene på arbeidsplassen kan avvike fra type testen, avhengig av temperatur, slitasje og nedbrytning.
- Ved bruk kan beskyttelseshandsker gi mindre motstand mot farlig kjemikalier som følge av endringer i fysiske egenskaper. Bevegelser, fasthuking, gnidning og nedbrytning forårsaket av kjemisk kontakt etc. kan redusere den faktiske brukstiden betydelig. For korrosive kjemikalier kan nedbrytning være den mest vesentlige faktoren som må vurderes ved valg av kjemikaliebestandige hansker.

Kontroller hanskene for eventuelle feil eller mangler før bruk.

EN 374-4:2013 nedbrytningsnivåer indikerer endringen i punkteringsmotstanden i hanskene etter eksponering mot testet kjemikalie.

VII. Dette produktet gir beskyttelse mot bakterier, sopp og virus. Hanskene er testet i henhold til ISO 16604:2014 (testmetoden benytter Phi-X174 bakteriofager) for å oppfylle kravene i BS EN ISO 374-5:2016 for resistens mot penetrasjon av blodbårne patogener. Gjennomtrengningsmotstanden er vurdert under laboratoriebetingelser og gjelder kun det testede prøveeksemplæret.

VIII. Komponenter benyttet i hanskeproduksjonen kan forårsake allergiske reaksjoner hos enkelte brukere. Hvis allergiske reaksjoner oppstår, søk medisinsk hjelp omgående.

Bruksanvisning for produktet

- Bruk – bare til engangsbruk. Hvis hanskene brukes om igjen, øker risikoen for forurensning og infeksjon på grunn av feil rengjøringsprosesser, og det er større risiko for at det oppstår hull og rifter ved gjenbruk fordi hanskene svekkes som følge av rengjøringsprosessene.
- Størrelse – velg riktig hanskestørrelsen til hånden din.
- Hansen tas på – hold hansen i kanten med én hånd. Juster hanskemøllene med tommelen på den andre hånden, og skyv hånden inn i hansen, en finger inn i hver hanskefinger. Dra i hanskens håndflate for å få god passform. Ta på den andre hansen på samme måte.
- Inspeksjon – det kan oppstå hull eller rifter etter at hanskene er tatt på. Undersøk begge hanskene etter at de er tatt på, og slutt å bruke dem umiddelbart hvis du finner skader.
- Under bruk – hansker som forurenses av blod eller andre organiske væsker, må fjernes umiddelbart og behandles som medisinsk avfall. Oppstår det hull eller rifter, må brukeren bytte hansker umiddelbart.
- Hvis det føles som om hanskene sitter løst rundt fingrene, bør brukeren bytte hansker.
- Hansen tas av – hold hansen i kanten, og trekk mot fingeren til hansen kommer av.

Oppbevaring

Oppbevares tørt og kjølig. Åpne bokser bør oppbevares skjermet fra lysstoffrer og direkte sollys.

Lagres helst i originalemballasjen under tørre forhold.

Ved lagring som anbefalt, vil de kjemiske egenskapene være uforandret i opptil tre år fra produksjonsdatoen. Levetid kan ikke spesifiseres da den avhenger av bruken. Det er brukers ansvar å fastslå om hansen er egnet for tiltenkt bruk.

955
ART. 114.955

GranberG®

955
ART. 114.955

GranberG®

CE 0321
PPE Cat. III

EN ISO 374-1:2016/Type B



EN ISO 374-5:2016

AQL 1.5



Available sizes: S, M, L, XL, XXL, XXXL
Tilgjengelige størrelser: S, M, L, XL, XXL, XXXL
Tillgängliga storlekar: S, M, L, XL, XXL, XXXL
Saatavilla olevat koot: S, M, L, XL, XXL, XXXL
Dostępane rozmiary: S, M, L, XL, XXL, XXXL

EN: USER MANUAL

NO: BRUKERVEILEDNING

SE: BRUKSANVISNING

FI: KÄYTTÖOHJE

PL: INSTRUKCJA OBSŁUGI

GranberG®

Head office:
GRANBERG AS
Bjoavegen 1442, NO-5584 Bjoa, Norway
Tel +47 53 77 53 00, e-mail post@granberg.no

Swedish office / European warehouse:
GRANBERG SVERIGE AB
Schubergvägen 20, 311 74 Falkenberg, Sweden
Tel +46 (0)346 124 25, e-mail post@granberg-ab.se

granberggloves.com

